

■ Parametry

Označení	Objednací číslo	Průtok vzduchu [m ³ /hod]	Statický tlak [Pa]	Akustický hluk [dB(A) 1m]	Příkon [W]	Napájecí napětí [V/Hz]	Otáčky [min ⁻¹]	Proud [A]	Max. teplota [°C]	Krytí výrobku [IP]	Hmotnost [kg]
VOX 200	15422	780	90	63	65	230/50	2700	0,30	70	X4	3,48
VOX 250	15433	1025	90	67	140	230/50	2600	0,70	70	X4	3,90
VOX 300	15421	2250	100	73	180	230/50	2600	0,80	70	X4	5,35
VOX 350	15486	4750	100	64	430	230/50	2500	2,00	45	X4	7,85
VOX 400	15519	5480	240	69	530	230/50	2500	2,40	40	X4	9,82
VOX 450	15434	4500	110	73	280	230/50	1380	1,25	40	X4	11,25
VOX 500	15609	6500	125	72	370	230/50	1380	1,75	60	X4	16,50
VOX 550	15610	7500	140	75	550	230/50	1350	2,60	60	X4	20,00
VOX 630	15621	10800	150	78	800	230/50	1300	3,70	60	X4	27,00

■ Příslušenství



KLIMAFLEX
ohybné hliníkové potrubí



RN, RNT
otočný regulátor otáček

